



P210E with optional Auto Start/Stop

**STANDARD FEATURES INCLUDE:**

- Direct drive ceramic plunger pump (unless noted)
- Powder coat plated frame with pneumatic / rubber wheels
- 50 ft. steel braid pressure hose with chemical injection (30 ft on P210E)
- Insulated lance with trigger gun
- Thermal sensor shield for high temperature-pump protection (excl P210E) OR thermo shut down avail on Gas Driven
- CSA approved (electric models)
- Avail from 2gpm-12gpm / 500psi – 5000psi



P550EAHT (5GPM @ 5000PSI, HI TEMP PUMP & TRIGGER GUN START)

**ELECTRIC DRIVEN COMMON SPEC'S**

MODEL	Flow GPM	Pressure PSI	Motor H.P.	Voltage		Total Amperage		Weight Lbs.
				1 Phase	3 Phase	1 Phase	3 Phase	
P210E	2.2	1000	1.5	120	-	12.1	-	66
P315E-1	3	1500	3	230	-	11.8	-	76
P411E-1	4	1100	3	230	-	17	-	145
P411E-3	4	1100	3	-	208/460/575	-	9.8/4.4/3	145
P419E-1	4	1900	5	230	-	22	-	160
P419E-3	4	1900	5	-	208/460/575	-	14.6/6.6/5	160
P429E-1	4	2900	7.5	230	-	33	-	185
P429E-3	4	2900	7.5	-	208/460/575	-	22.5/9.8/7.5	185
P440E-3	4	4000	10	-	208/460/575	-	29/12.5/10	250
P562E-1	5.6	2000	7.5 (Belt)	230	-	33	-	185
P562E-3	5.6	2000	7.5 (Belt)	-	208/460/575	-	22.5/10/7.5	185
P820E-3	8	2000	10 (Belt)	-	208/460/575	-	29/12.5/10	250

**GASOLINE DRIVEN COMMON SPEC'S**

Model	GPM	PSI	HP	Pump	Wheel Size
P325G2	3.0	2500	6.5	General	8 inch
P430G2	4.0	3000	13	General	10 inch



P325G2

**COMMON FACTORY ADDED OPTIONS:**

- Auto start/stop Trigger gun activated stop/start control circuit with solid state time delay shutdown (electric driven models)
- Throttle control automatic engine speed reduction (gasoline driven models)
- Wet sandblast kit
- Drain cleaning kit
- Rotary nozzle / Hose reel
- Special application design with factory consultation



P430G2